



www.ecorubberedenvale.co.za

+27 11 447 9842

ECO ACRYLIC SEALANT INFO SHEET

PRODUCT DESCRIPTION	<ul style="list-style-type: none"> * Eco Rubber Sealant is a waterproofing barrier coating, formulated on an elastomeric polymer base. * This water-borne coating boast with cutting edge technology where the formulation is highly UV resistant. * Eco Rubber provides superior adhesion that proof to resist weathering, chalking and cracking. * This product create a waterproofing membrane barrier that is UV reflective and prevent corrotion on metal substrates. * The external sealant proofs to show signifucant reduction in colour fading due to the oxside colouring technology that is applied.
----------------------------	--

PRODUCT BENEFITS	<ul style="list-style-type: none"> * Improves life span of substrates that were coated * Waterproofing at it's best!! * Corrotion control * Encapsulation (Asbestos) * Highly stretchable and contract to its original form, therefore with standing thermal cycling. * No solvents, there for it is Enviromentally Friendly and can be applied were rainwater is harvested. * No negative effect on human or animal life. * Waterproofing that can with stand ponding. * Can be applied to all construction materials,even Architectural dufficult area such as services gantrees. * Tube applied * Total ambient temperature application, no heating or prophane flame heating required.
-------------------------	---

MATERIAL APPLICATION

SURFACE PREPARATION	<ul style="list-style-type: none"> * Surfaces to be sprayed / painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign materials. Allow all surfaces to dry completely prior to painting. * Avoid application when the moisture is above 15% * Remove all unstable paint film. * Repair defected surfaces before application.
MATERIAL	Single component, ready-to-use from container with little stirring required.
APPLICATION TEMPERATURE RANGE	Above 10°C
RECOATING	Excellent
PRIMARY CURE	3 hours at 25°C
FINAL CURE TIME	3 - 5 Days
THINNER (VOLUME)	Must NOT be thinned

TECHNICAL DATA

PARAMETER	Pure Acrylic Polymer
FINISH	Homogeneous: smooth, various colours
SELF PRIMER	Positive
PH	8.72
VISCOSITY	250ku
SPECIFIC GRAVITY	1.18
TOXICITY	Material is non-toxic & requires no special ventilation during application. Contains no
FLAMMABILITY	Non-flammable. Does not support flame spread. Class 3
PACKAGE STABILITY	One year + after opening: no settling or other undesirable effects.
ABRASION RESISTANCE	Medium to High. Not suitable for high traffic areas
ELONGATION	70% with a 100% full memory
FUNGUS RESISTANCE	No fungus growth when material tested in an environment of three organisms.
V.O.C	78 grams per Litre
WATER, %	11%
SOLIDS BY MASS	52%
TSC	64%
FISH EYE TEST	Non - Passed
FILM HARDNESS	Flexible will not harden over time
FLASH POINT	Water borne - not flammable
FIRE INDEX	Class 3
UV RESISTANCE	Will start to degrade after 7 - 10 + years

STANDARD PACKAGING

PACKAGING	280ml tube
------------------	------------

HEALTH & SAFETY

SAFETY PRECAUTIONS	<ul style="list-style-type: none">* Keep container tightly closed and keep out of reach of children or away from food and drink.* In case of contact with eye, rinse with plenty of water immediately and seek medical advice.* Remove splashes from skin by using soap or water.* Always keep container in a secure upright position.* Dispose off any paint waste in accordance with the appropriate EHS Regulations
---------------------------	--

NOTE: We warranty only the quality of our product and the data sheet is based on results obtained from experience and tests.

We reserve the right to change data without prior notice.